	SHIRTS							
Style	Pocket	Material	Color	Striping	Class / Type	Standard/Specification	Picture for Example Only	
HI-VIS SHORT SLEEVE T-SHIRT	Minimum one chest pocket	Non-melting (eg. 100% cotton)	Yellow	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms	ANSI - TYPE R / CLASS 2 CSA - CLASS 2 / LEVEL 2	ANSI 107 CSA Z96		
HI-VIS SHORT SLEEVE BUTTON DOWN SHIRT	Two chest pockets	Non-melting (eg. 100% cotton)	Yellow	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms	ANSI - TYPE R / CLASS 2 CSA - CLASS 2 / LEVEL 2	ANSI 107 CSA Z96		
HI-VIS LONG SLEEVE T-SHIRT	Minimum one chest pocket	Non-melting (eg. 100% cotton) Also available in chemical resistant	Yellow	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms	ANSI - TYPE R / CLASS 3 CSA - CLASS 2 / LEVEL 2	ANSI 107 CSA Z96 ISO 16602		
HI-VIS LONG SLEEVE BUTTON DOWN SHIRT	Two chest pockets	Non-melting (eg. 100% cotton) Also available in chemical resistant	Yellow	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms	ANSI - TYPE R / CLASS 3 CSA - CLASS 2 / LEVEL 2	ANSI 107 CSA Z96 ISO 16602		
ARC FLASH - HI-VIS LONG SLEEVE T- SHIRT	Minimum one chest pocket	FR blend Fabric and components must meet performance standard for FR rating Minimum APTV - 8 calories/cm ²	Yellow Grey (Brazil)	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms	ANSI - TYPE R / CLASS 3 CSA - CLASS 2 / LEVEL 2 Min APTV 8 cal/cm ²	ANSI 107 CSA Z96 For FR performance - ASTM F1506, NFPA70E, CSAZ462		
ARC FLASH - HI-VIS LONG SLEEVE BUTTON DOWN SHIRT	Two chest pockets	FR blend Fabric and components must meet performance standard for FR rating Minimum APTV - 8 calories/cm ²	Yellow Grey (Brazil)	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms	ANSI - TYPE R / CLASS 3 CSA - CLASS 2 / LEVEL 2 Min APTV 8 cal/cm ²	ANSI 107 CSA 296 For FR performance - ASTM F1506, NFPA70E, CSAZ462		

PANTS								
Style	Pocket	Material	Color	Striping	Class / Type	Standard/Specification	Picture for Example Only	
KHAKI / CHINO / CARGO STYLE	Two front and two back pockets and side pockets on legs	Non-melting (eg. 100% cotton) Also available in chemical resistant	Dark blue	Include at least 25mm (1") wide stripes/bands of	Combined with shirt: ANSI - TYPE R / CLASS 3 CSA - CLASS 3 / LEVEL 2	ANSI 107 CSA 296 ISO 16602		
ARC FLASH - KHAKI / CHINO / CABGO STYLE	Two front and two back pockets and side pockets on legs	FR blend Fabric and components must meet performance standard for FR rating Minimum APTV - 8 calories/cm ²		Include at least 25mm (1") wide stripes/bands of	Combined with shirt: ANSI - TYPE R / CLASS 3 CSA - CLASS 3 / LEVEL 2 Min APTV 8 cal/cm ²	For FR performance - ASTM F1506, NFPA70E, CSAZ462		

Two front and two JEANS back pockets and D side pockets on legs	Denim / non-melting D	Dark blue	Include at least 25mm (1") wide stripes/bands of	Combined with shirt:	ANSI 107 CSA Z96	A
---	-----------------------	-----------	--	----------------------	---------------------	---

COVERALLS								
Style	Pocket	Material	Color	Striping	Class / Type	Standard/Specification	Picture for Example Only	
HI-VIS COVERALL	access slots, two front and rear (each) pants pockets, and	Non-melting (eg. 100% cotton) Also available in chemical resistant	Yellow	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms and both legs	ANSI - TYPE R / CLASS 3 CSA - CLASS 3 / LEVEL 2	ANSI 107 CSA Z96 ISO 16602		
ARC FLASH - HI-VIS COVERALL	two front pants access slots, two front and rear (each) pants pockets, and	must meet performance standard for FR rating	Yellow Grey (Brazil)	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms and both legs	CSA - CLASS 3 / LEVEL 2	ANSI 107 CSA 296 For FR performance - ASTM F1506, NFPA70E, CSAZ462		

OUTERWEAR							
Style	Pocket	Material	Color	Striping	Class / Type	Standard/Specification	Picture for Example Only
HI-VIS HOODED SWEATER - ZIPPER FRONT - REMOVABLE HOOD	Two front pockets	Non-melting (eg. 100% cotton) Also available in chemical resistant	Yellow	symmetric X on back from shoulders to the waist	REMOVABLE HOOD ANSI - TYPE R / CLASS 2 CSA - CLASS 2 / LEVEL 2	ANSI 107 CSA 296 ISO 16602	
ARC FLASH - HI-VIS HOODED SWEATER - ZIPPER FRONT - REMOVABLE HOOD	Two front pockets	must meet performance standard for FR rating	Yellow	Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist	REMOVABLE HOOD ANSI - TYPE R / CLASS 2 CSA - CLASS 2 / LEVEL 2 Min APTV 8 cal/cm2	ANSI 107 CSA 296 For FR performance - ASTM F1506, NFPA70E, CSAZ462	
ARC FLASH - UNLINED BOMBER JACKET	Two front pockets	must meet performance standard for FR rating	Yellow	Solid / 50mm (2"); 360 degree visibility; Include full waist level horizontal / 2 vertical on the front from waist stripe over the shoulders, symmetric X on back from shoulders to the waist stripe, stripes around both arms	ANSI - TYPE R / CLASS 2 CSA - CLASS 2 / LEVEL 2 Min APTV 8 cal/cm2	ANSI 107 CSA 296 For FR performance - ASTM F1506, NFPA70E, CSAZ462	