



Definitions

EHSS-Phos Program – Walking Working Surfaces, Appendix A

The following table defines key terms used in the *EHSS-Phos Walking Working Surfaces* program:

Term	Definition
Aisle	Designated and marked passage for inside traffic.
Attendant	Person who has received documented training in proper procedures and designated to perform a specific task of monitoring the hazard. The Attendant's sole responsibility is to assure that no unauthorized or unprotected personnel enter a restricted area.
Cleanliness	An area is clean when it is free of trash, debris, dirt, stains, or impurities (unsoiled).
Dockboard	An engineered device that may be portable or built into a loading dock to allow access from the loading dock to a transport vehicle.
Egress	Continuous and unobstructed way of exit travels from any point of a building or structure to a public way and consists of three (3) separate and distinct parts: (1) the exit access, (2) the exit, (3) the exit discharge. A means of egress comprises the vertical and horizontal travel and shall include intervening room spaces, doorways, hallways, corridors, passageways, balconies, ramps, stairs, enclosures, lobbies, escalators, horizontal exits, courts and yards.
Elevator	Permanent hoisting and lowering mechanism with a car or platform moving vertically in guides and serving two or more floors of a structure. The term excludes such devices as conveyers, tiering, or piling machines, material hoists, skip or furnace hoists, wharf ramps, lift bridges, car lifts, and dumpers.
Engineer	Licensed Professional Engineer employed by the Company or an appropriately licensed contractor, authorized by the Company to perform engineering work.
Fixed Ladder	Vertical means of egress permanently attached to a structure, building or piece of equipment.
Floor	Surface of a room or structure on which one stands. This includes the lower or supporting surface of a structure or the surface of a structure on which vehicles travel.
Floor Hole	Any hole measuring less than 12 inches but more than 1 inch in any floor, platform, pavement, or yard.



Definitions

EHSS-Phos Program – Walking Working Surfaces, Appendix A

Term	Definition
Floor opening	Any opening measuring 12 inches by 12 inches or greater in any floor, platform, pavement, or yard, and having a drop of 4 feet or more into which a person can fall .
Guardrail	Barrier to prevent persons from walking, stepping, falling or coming in contact with a hazard, opening or hole. It can be a handrail, stair rail, or substantially constructed hard barricade. It can consist of materials such as scaffolding components, 2X4 wood framing, angle iron, and steel/chain which meet Standards & Specifications, <i>STF 05520 Details for Pipe Railing for Walking and Working Surfaces & STF 05521 Details for Angle Railing for Walking and Working Surfaces</i> . https://doculink.mosaicco.com/livelink/lisapi.dll?func=ll&objId=838715&objAction=browse&viewType=1
Handrail	Rail used to provide persons with a handhold for support.
Hard barricade	A solid, OSHA approved physical barrier or structure to prevent the entry of persons to an area and/or prevent personnel from being exposed to a hazard.
Housekeeping	Process that includes cleanliness, orderliness, and proper arrangement of materials.
Industrial Stairway	Interior and exterior stairs serving machinery, tanks, equipment, and stairs to or from floors, platforms or pits. This section does not apply to: stairs used for fire exit purposes, construction operations, or articulated stairs.
Ladder safety system	A system attached to a fixed ladder designed to eliminate or reduce the possibility of a worker falling off the ladder. A ladder safety system usually consists of a carrier, safety sleeve, lanyard, connectors, and body harness. Cages and wells are not considered ladder safety systems.
Orderliness	An area is in order when there are no unnecessary things about and all necessary things are in their proper place.
Platform	Horizontal surface raised above, located below or extended beyond the level or limits of the adjacent area.
Stair rail	Vertical barrier erected along the unprotected sides and edges of a stairway to prevent persons from falling to lower levels.



Definitions

EHSS-Phos Program – Walking Working Surfaces, Appendix A

Term	Definition
Standards and Specifications	Mosaic Fertilizers current approved Standards and Specifications https://doculink.mosaicco.com/livelink/lisapi.dll?func=ll&objId=838715&objAction=browse&viewType=1 : STE05530 Grating Design Guide STF05530 Grating Fabrication Details STF05520 Details for Pipe Railing for Walking and Working Surfaces STF05521 Details for Angle Railing for Walking and Working Surfaces STE05501 Fixed Ladders Design Guide STF05501 Fixed Ladders Fabrication Details
Soft barricade	Approved tape used as a temporary barrier to prevent or restrict access to an area.
Toe board	Floor level barrier designed to prevent materials from sliding off or falling off a platform or step.
Wall hole	Any hole that is less than 30 inches but more than 1 inch of any width, in a wall or partition.
Wall opening	An opening at least 30 inches high and 18 inches wide , in a wall or partition, and having a drop of 4 feet or more into which a person can fall.